Chemstore®
HAZARDOUS MATERIALS EXPERTS

Chemstore UK
Tooting Works Business Centre
89 Bickersteth Rd
London SW17 9SH
0208 704 1807
www.chemstore.co.uk
sales@chemstore.co.uk

16 Drum Firevault

- 90-Minute Fire-Rated Construction
- Fully Bunded, Tested & Certified
- Vandal Proof
- Maintenance Free
- Fork-Liftable
- Optional-Extras Available

Firevault

Storage	16 x 210L Drums or 4 x 1000L IBC's/Pallets on two levels
Dimensions	3360(L) x 2130(D) x 3250(H) mm
Bunds	Capacity: **1100L.** Capacity exceeds Environmental guidelines, 25% of the total volume and 110% of the single largest container. Hydrostatic test certificates issued through **Chempli**.

Chemstore UK
Tooting Works Business Centre
89 Bickersteth Rd
London SW17 9SH
0208 704 1807
www.chemstore.co.uk
sales@chemstore.co.uk

16 Drum Firevault

Ventilation	Intumescent Pyrogrilles at high and low level, ensure good natural ventilation. Pyrogrilles are tested and certified to BS 476 part 22.
Wall/Door Cladding	100mm Thick Fire-rated panels are high quality resin bonded Conrock slab, securely fixed using the tongue and groove method, to the robust welded steel box framework. When tested in accordance with BS 476 part 22 1987 the panels exhibit the following results: • Resistance to the passage of flames 98 mins. • Insulation on temperature 98 mins. • Stability >98 mins Therefore, overall fire resistance of 98 mins.
Roof Cladding	Double skin lighter weight fire panel on roof, in accordance with HS(G)51, to act as explosion relief.
Finish	Framework: 2-pack anti-corrosive paint system. Choice of colours. Standard is Red RAL 3020. **External:** Longlife, maintenance-free plastisol (PVC) finish on wall panels. Choice of colours. Standard colour: Goosewing Grey. **Internal:** White chemical-resistant (PVC) finish on internal walls. Anti-static and food safe finish
Signage	Clear and bold “Firevault”, “Flammable, No Smoking, No Naked Light” and “Keep Door Closed When Not In Use” signs fitted as standard.