Chemstore®
HAZARDOUS MATERIALS EXPERTS

**Chemstore UK**
Tooting Works Business Centre
89 Bickersteth Rd
London SW17 9SH
0208 704 1807
www.chemstore.co.uk
sales@chemstore.co.uk

# 48 Drum Firevault

- 90-Minute Fire-Rated Construction
- Fully Bunded, Tested & Certified
- Vandal Proof
- Maintenance Free
- Fork-Liftable
- Optional-Extras Available

Firevault

| | |
|---|---|
| **Storage** | 48 x 210L Drums or 12 x 1000L IBC's/Pallets on two levels |
| **Dimensions** | 9000(L) x 2130(D) x 3250(H) mm |
| **Bunds** | Capacity: **3300L.** Capacity exceeds Environmental guidelines, 25% of the total volume and 110% of the single largest container.<br>Hydrostatic test certificates issued through **Chempli**. |

**Chemstore UK**
Tooting Works Business Centre
89 Bickersteth Rd
London SW17 9SH
0208 704 1807
www.chemstore.co.uk
sales@chemstore.co.uk

# 48 Drum Firevault

| | |
|---|---|
| **Ventilation** | Intumescent Pyrogrilles at high and low level, ensure good natural ventilation.<br>Pyrogrilles are tested and certified to BS 476 part 22. |
| **Wall/Door Cladding** | 100mm Thick Fire-rated panels are high quality resin bonded Conrock slab, securely fixed using the tongue and groove method, to the robust welded steel box framework.<br><br>When tested in accordance with BS 476 part 22 1987 the panels exhibit the following results:<br>• Resistance to the passage of flames 98 mins.<br>• Insulation on temperature 98 mins.<br>• Stability >98 mins<br><br>Therefore, overall fire resistance of 98 mins. |
| **Roof Cladding** | Double skin lighter weight fire panel on roof, in accordance with HS(G)51, to act as explosion relief. |
| **Finish** | Framework: 2-pack anti-corrosive paint system.<br>Choice of colours. Standard is Red RAL 3020.<br><br>**External:** Longlife, maintenance-free plastisol (PVC) finish on wall panels.<br>Choice of colours. Standard colour: Goosewing Grey.<br><br>**Internal:** White chemical-resistant (PVC) finish on internal walls.<br>Anti-static and food safe finish |
| **Signage** | Clear and bold “Firevault”, “Flammable, No Smoking, No Naked Light” and “Keep Door Closed When Not In Use” signs fitted as standard. |